CLC-Grundlack farblos MV 100:15 GT mit CLC-Härter 10



Date of last issue: 04.11.2020 Version **Revision Date:** 12.07.2022 1.5 Date of first issue: 02.03.2018

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : CLC-Grundlack farblos

Identification of the article : 101465oiu53

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-Industrial paint

stance/Mixture

1.3 Details of the supplier of the safety data sheet

WT-Direct GmbH Company

Thujastraße 45

DE - 73614 Schorndorf Telephone : +49 (0) 7181 / 9854840 Telefax : +49 (0) 7181 / 98548422

E-mail address of person

responsible for the SDS

: info@wt-direct.de

1.4 Emergency telephone number

Emergency telephone

number

Phone: +49 (0) 7181/9854840

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

Flammable liquids, Category 3 H226: Flammable liquid and vapour.

Skin irritation, Category 2 H315: Causes skin irritation.

Eye irritation, Category 2 H319: Causes serious eye irritation. H336: May cause drowsiness or dizziness.

Specific target organ toxicity - single ex-

posure, Category 3, Central nervous

system

Specific target organ toxicity - repeated

longed or repeated exposure.

exposure, Category 2

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

H373: May cause damage to organs through pro-

CLC-Grundlack farblos MV 100:15 GT mit CLC-Härter 10



Version Revision Date:
Date of last issue: 04.11.2020
1.5 Date of first issue: 02.03.2018

Hazard pictograms :







Signal word : Warning

Hazard statements : H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or

repeated exposure.

Precautionary statements : Prevention:

P210 Keep away from heat, hot surfaces, sparks, open

flames and other ignition sources. No smoking.

P260 Do not breathe mist or vapours.P264 Wash skin thoroughly after handling.

P280 Wear protective gloves/ protective clothing/ eye protec-

tion/ face protection/ hearing protection.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immedi-

ately all contaminated clothing. Rinse skin with water.

P370 + P378 In case of fire: Use dry sand, dry chemical or

alcohol-resistant foam to extinguish.

Hazardous components which must be listed on the label:

Butyl acetate

Xylene

2-Propanol, 1-methoxy-, acetate

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : Industrial paint

Components

Chemical name	CAS-No.	Classification	Concentration
	EC-No. Index-No.		(% w/w)
	Registration number		
Butyl acetate	123-86-4	Flam. Liq. 3; H226	>= 30 - < 50
		STOT SE 3; H336	
	01-2119485493-29	(Central nervous	
		system)	

CLC-Grundlack farblos MV 100:15 GT mit CLC-Härter 10



Version Revision Date: Date of last issue: 04.11.2020 1.5 Date of first issue: 02.03.2018

		EUH066	
Xylene	1330-20-7 01-2119488216-32	Flam. Liq. 3; H226 Acute Tox. 4; H332 Acute Tox. 4; H312 Skin Irrit. 2; H315 Eye Irrit. 2; H319 STOT SE 3; H335 (Respiratory system) STOT RE 2; H373 Asp. Tox. 1; H304 Aquatic Chronic 3; H412	>= 10 - < 20
Ethylbenzene	100-41-4 01-2119489370-35	Flam. Liq. 2; H225 Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2; H319 STOT RE 2; H373 (hearing organs) Asp. Tox. 1; H304 Aquatic Chronic 3; H412	>= 2,5 - < 10
2-Propanol, 1-methoxy-, acetate	108-65-6 01-2119475791-29	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system)	>= 1 - < 10
Toluene	108-88-3 01-2119471310-51	Flam. Liq. 2; H225 Skin Irrit. 2; H315 Repr. 2; H361d STOT SE 3; H336 (Central nervous system) STOT RE 2; H373 Asp. Tox. 1; H304	>= 0,1 - < 1

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : Move out of dangerous area.

Show this safety data sheet to the doctor in attendance.

Do not leave the victim unattended.

If inhaled : If unconscious, place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

In case of skin contact : If skin irritation persists, call a physician.

If on skin, rinse well with water. If on clothes, remove clothes.

CLC-Grundlack farblos MV 100:15 GT mit CLC-Härter 10



Date of last issue: 04.11.2020 Version Revision Date: 12.07.2022 1.5 Date of first issue: 02.03.2018

In case of eye contact Immediately flush eye(s) with plenty of water.

> Remove contact lenses. Protect unharmed eye.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed Keep respiratory tract clear.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician. Take victim immediately to hospital.

4.2 Most important symptoms and effects, both acute and delayed

Risks Causes skin irritation.

> Causes serious eve irritation. May cause drowsiness or dizziness.

May cause damage to organs through prolonged or repeated

exposure.

4.3 Indication of any immediate medical attention and special treatment needed

No information available. Treatment

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Alcohol-resistant foam

Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-

fighting

Do not allow run-off from fire fighting to enter drains or water

courses.

ucts

Hazardous combustion prod- : No hazardous combustion products are known

5.3 Advice for firefighters

for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

Further information Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

For safety reasons in case of fire, cans should be stored sepa-

CLC-Grundlack farblos MV 100:15 GT mit CLC-Härter 10



Version Revision Date: Date of last issue: 04.11.2020 1.5 Date of first issue: 02.03.2018

rately in closed containments.

Use a water spray to cool fully closed containers.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.

Remove all sources of ignition. Evacuate personnel to safe areas.

Beware of vapours accumulating to form explosive concentra-

tions. Vapours can accumulate in low areas.

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible ab-

sorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local

/ national regulations (see section 13).

6.4 Reference to other sections

Not applicable

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Avoid formation of aerosol.

Do not breathe vapours/dust.

Avoid exposure - obtain special instructions before use.

Avoid contact with skin and eyes. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Open drum carefully as content may be under pressure. Dispose of rinse water in accordance with local and national

regulations.

Advice on protection against

fire and explosion

Do not spray on a naked flame or any incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Keep away from open flames, hot surfaces and sources of ignition.

Hygiene measures : When using do not eat or drink. When using do not smoke.

Wash hands before breaks and at the end of workday.

CLC-Grundlack farblos MV 100:15 GT mit CLC-Härter 10



Version Revision Date:
Date of last issue: 04.11.2020
1.5 Date of first issue: 02.03.2018

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.

Further information on stor-

age stability

No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) : No information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

CAS-No.	Value type (Form	Control parameters	Basis		
	of exposure)				
123-86-4	TWA	150 ppm	GB EH40		
		724 mg/m3			
	STEL	200 ppm	GB EH40		
		966 mg/m3			
	TWA	50 ppm	2019/1831/E		
		241 mg/m3	U		
Further inforn	Further information: Indicative				
	STEL	150 ppm	2019/1831/E		
		723 mg/m3	U		
Further inforr	nation: Indicative		1		
1330-20-7	TWA	50 ppm	2000/39/EC		
		221 mg/m3			
Further inforr	Further information: Identifies the possibility of significant uptake through the				
skin, Indicative			-		
	STEL	100 ppm	2000/39/EC		
		442 mg/m3			
Further inforr	Further information: Identifies the possibility of significant uptake through the				
skin, Indicativ	/e				
100-41-4	TWA	100 ppm	GB EH40		
		441 mg/m3			
Further inforr	Further information: Can be absorbed through the skin. The assigned sub-				
stances are those for which there are concerns that dermal absorption will			sorption will		
lead to syster	lead to systemic toxicity.				
	STEL	125 ppm	GB EH40		
Further information: Can be absorbed through the skin. The assigned sub-					
	stances are those for which there are concerns that dermal absorption will				
j	TWA	100 ppm	2000/39/EC		
		442 mg/m3			
Further inforr	nation: Identifies the	possibility of significant uptal	ke through the		
	Further informulation Further informulation Further informulation Further informulation Further informulation Further informulation 100-41-4 Further informulation Further informulation Further informulation stances are to lead to system Further informulation stances are to lead to system Further informulation Further informulation stances are to lead to system Further informulation Further informulation Further informulation Stances are to lead to system Further informulation Further informulation Further informulation Further informulation Further informulation Stances are to lead to system Further informulation Further informula	of exposure) 123-86-4 TWA STEL TWA Further information: Indicative STEL Further information: Indicative 1330-20-7 TWA Further information: Identifies the skin, Indicative STEL Further information: Identifies the skin, Indicative 100-41-4 TWA Further information: Can be absor stances are those for which there lead to systemic toxicity. STEL Further information: Can be absor stances are those for which there lead to systemic toxicity. TWA	123-86-4 TWA 150 ppm 724 mg/m3		

CLC-Grundlack farblos MV 100:15 GT mit CLC-Härter 10



Version Revision Date: Date of last issue: 04.11.2020 1.5 Date of first issue: 02.03.2018

	skin, Indicativ	re				
		STEL	200 ppm 884 mg/m3	2000/39/EC		
	Further information: Identifies the possibility of significant uptake through the skin, Indicative					
2-Propanol, 1-methoxy-, acetate	108-65-6	TWA	50 ppm 274 mg/m3	GB EH40		
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.					
		STEL	100 ppm 548 mg/m3	GB EH40		
	stances are t	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.				
		TWA	50 ppm 275 mg/m3	2000/39/EC		
	Further information: Identifies the possibility of significant uptake through the skin, Indicative					
		STEL	100 ppm 550 mg/m3	2000/39/EC		
	Further information: Identifies the possibility of significant uptake through the skin, Indicative					
Toluene	108-88-3	TWA	50 ppm 191 mg/m3	GB EH40		
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.					
		STEL	100 ppm 384 mg/m3	GB EH40		
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.					
		TWA	50 ppm 192 mg/m3	2006/15/EC		
	Further information: Indicative, Identifies the possibility of significant uptake through the skin					
		STEL	100 ppm 384 mg/m3	2006/15/EC		
	Further inform through the s		entifies the possibility of sig	gnificant uptake		

Biological occupational exposure limits

-	-			
Substance name	CAS-No.	Control parameters	Sampling time	Basis
Xylene	1330-20-7	methyl hippuric acid: 650 Millimo- les per mole Creat- inine (Urine)	After shift	GB EH40 BAT
		(Ullie)		

8.2 Exposure controls

Personal protective equipment

CLC-Grundlack farblos MV 100:15 GT mit CLC-Härter 10



Version Revision Date: Date of last issue: 04.11.2020 1.5 12.07.2022 Date of first issue: 02.03.2018

Eye protection : Eye wash bottle with pure water

Tightly fitting safety goggles

Wear face-shield and protective suit for abnormal processing

problems.

Hand protection

Remarks : The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Skin and body protection : Impervious clothing

Choose body protection according to the amount and concen-

tration of the dangerous substance at the work place.

Respiratory protection : In the case of vapour formation use a respirator with an ap-

proved filter.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : liquid

pH : No data available

Boiling point/boiling range : > 36 °C

Flash point : 29 °C

Evaporation rate : No data available

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower :

flammability limit

No data available

Vapour pressure : < 1.000 hPa (50 °C)

Relative vapour density : No data available

Density : 0,974 g/cm3 (23 °C)

Solubility(ies)

Water solubility : partly soluble
Partition coefficient: n- : No data available

octanol/water

Auto-ignition temperature : No data available

Decomposition temperature : Not applicable

Viscosity

Viscosity, kinematic : > 20,6 mm2/s (40 °C)

Flow time : 28 s

Cross section: 4 mm Method: DIN 53211

Explosive properties : No data available

CLC-Grundlack farblos MV 100:15 GT mit CLC-Härter 10



Version Revision Date:
Date of last issue: 04.11.2020
1.5 Date of first issue: 02.03.2018

Oxidizing properties : No data available

9.2 Other information

Self-ignition : No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : No dangerous reaction known under conditions of normal use.

No decomposition if stored and applied as directed.

Vapours may form explosive mixture with air.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : Strong oxidizing agents

10.6 Hazardous decomposition products

Stable under recommended storage conditions.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Not classified based on available information.

Product:

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l

Exposure time: 4 h
Test atmosphere: vapour
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 2.000 mg/kg

Method: Calculation method

Skin corrosion/irritation

Causes skin irritation.

CLC-Grundlack farblos MV 100:15 GT mit CLC-Härter 10



Version Revision Date:
Date of last issue: 04.11.2020
1.5 Date of first issue: 02.03.2018

Product:

Remarks : May cause skin irritation in susceptible persons.

Serious eye damage/eye irritation

Causes serious eye irritation.

Product:

Remarks : May cause irreversible eye damage.

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

May cause drowsiness or dizziness.

STOT - repeated exposure

May cause damage to organs through prolonged or repeated exposure.

Aspiration toxicity

Not classified based on available information.

Further information

Product:

Remarks : Solvents may degrease the skin.

SECTION 12: Ecological information

12.1 Toxicity

No data available

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

CLC-Grundlack farblos MV 100:15 GT mit CLC-Härter 10



Version Revision Date:
Date of last issue: 04.11.2020
1.5 Date of first issue: 02.03.2018

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher.

12.6 Other adverse effects

Product:

Endocrine disrupting poten-

tial

The substance/mixture does not contain components considered to have endocrine disrupting properties according to

REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

Additional ecological infor-

mation

No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Do not dispose of waste into sewer.

Do not contaminate ponds, waterways or ditches with chemi-

cal or used container.

Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty drum.

SECTION 14: Transport information

14.1 UN number

ADN : UN 1263
ADR : UN 1263
RID : UN 1263
IMDG : UN 1263
IATA : UN 1263

14.2 UN proper shipping name

ADN : PAINT
ADR : PAINT
RID : PAINT

CLC-Grundlack farblos MV 100:15 GT mit CLC-Härter 10



Version Revision Date:
Date of last issue: 04.11.2020
1.5 Date of first issue: 02.03.2018

IMDG : PAINT IATA : PAINT

14.3 Transport hazard class(es)

ADN : 3
ADR : 3
RID : 3
IMDG : 3
IATA : 3

14.4 Packing group

ADN

Packing group : III
Classification Code : F1
Hazard Identification Number : 30
Labels : 3

ADR

Packing group : III
Classification Code : F1
Hazard Identification Number : 30
Labels : 3
Tunnel restriction code : (D/E)

RID

Packing group : III
Classification Code : F1
Hazard Identification Number : 30
Labels : 3

IMDG

Packing group : III
Labels : 3
EmS Code : F-E, <u>S-E</u>

IATA (Cargo)

Packing instruction (cargo : 366

aircraft)

Packing instruction (LQ) : Y344
Packing group : III

Labels : Flammable Liquids

IATA (Passenger)

Packing instruction (passen: 355

ger aircraft)

Packing instruction (LQ) : Y344
Packing group : III

Labels : Flammable Liquids

14.5 Environmental hazards

ADN

Environmentally hazardous : no

CLC-Grundlack farblos MV 100:15 GT mit CLC-Härter 10



Version Revision Date:
Date of last issue: 04.11.2020
1.5 Date of first issue: 02.03.2018

ADR

Environmentally hazardous : no

RID

Environmentally hazardous : no

IMDG

Marine pollutant : no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances,

mixtures and articles (Annex XVII)

Conditions of restriction for the following entries should be considered:

Number on list 3

Toluene (Number on list 48)

REACH - Candidate List of Substances of Very High

Concern for Authorisation (Article 59).

Regulation (EC) No 1005/2009 on substances that de-

plete the ozone layer

Regulation (EU) 2019/1021 on persistent organic pollu-

tants (recast)

UK REACH List of substances subject to authorisation

(Annex XIV)

GB Export and import of hazardous chemicals - Prior

Informed Consent (PIC) Regulation

Not applicable

Not applicable

Not applicable

: Not applicable

: Not applicable

FLAMMABLE LIQUIDS

Seveso III Directive (2012/18/EU) implemented P5c

by Control of Major Accident Hazards Regula-

tions 2015 (COMAH)

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial

emissions (integrated pollution prevention and control) Volatile organic compounds (VOC) content: 59,09 %

Volatile CMR compounds: < 0,01 %

15.2 Chemical safety assessment

A Chemical Safety Assessment is not required for this substance.

CLC-Grundlack farblos MV 100:15 GT mit CLC-Härter 10



Version Revision Date:
Date of last issue: 04.11.2020
1.5 Date of first issue: 02.03.2018

SECTION 16: Other information

Full text of H-Statements

H225 : Highly flammable liquid and vapour.
H226 : Flammable liquid and vapour.

H304 : May be fatal if swallowed and enters airways.

H312 : Harmful in contact with skin.

H315 : Causes skin irritation.

H319 : Causes serious eye irritation.

H332 : Harmful if inhaled.

H335
H336
H361d
May cause respiratory irritation.
May cause drowsiness or dizziness.
Suspected of damaging the unborn child.

H373 : May cause damage to organs through prolonged or repeated

exposure.

H412 : Harmful to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox. : Acute toxicity

Aquatic Chronic : Long-term (chronic) aquatic hazard

Asp. Tox. : Aspiration hazard

Eye Irrit. : Eye irritation

Flam. Liq. : Flammable liquids

Repr. : Reproductive toxicity

Skin Irrit. : Skin irritation

STOT RE : Specific target organ toxicity - repeated exposure STOT SE : Specific target organ toxicity - single exposure

2000/39/EC : Europe. Commission Directive 2000/39/EC establishing a first

list of indicative occupational exposure limit values

2006/15/EC : Europe. Indicative occupational exposure limit values

2019/1831/EU : Europe. Commission Directive 2019/1831/EU establishing a

fifth list of indicative occupational exposure limit values

GB EH40 : UK. EH40 WEL - Workplace Exposure Limits
GB EH40 BAT : UK. Biological monitoring guidance values

2000/39/EC / TWA : Limit Value - eight hours 2000/39/EC / STEL : Short term exposure limit 2006/15/EC / TWA : Limit Value - eight hours 2006/15/EC / STEL : Short term exposure limit 2019/1831/EU / TWA : Limit Value - eight hours 2019/1831/EU / STEL : Short term exposure limit

GB EH40 / TWA : Long-term exposure limit (8-hour TWA reference period)
GB EH40 / STEL : Short-term exposure limit (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good La-

CLC-Grundlack farblos MV 100:15 GT mit CLC-Härter 10



Version Revision Date:
Date of last issue: 04.11.2020
1.5 Date of first issue: 02.03.2018

boratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECI -Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Classification of the mixture:

Classification procedure:

Flam. Liq. 3	H226	Based on product data or assessment
Skin Irrit. 2	H315	Calculation method
Eye Irrit. 2	H319	Calculation method
STOT SE 3	H336	Calculation method
STOT RE 2	H373	Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN